

Παρακαλούμε για επικαιροποιημένες τιμές ζητήστε το καινούριο τιμοκατάλογο ή προ

TIMOKATALOGOS WAGO

RELAYS 24VDC

ΤΑΞΙΝΟΜΗΣΗ ΑΝΑ ΚΑΤΗΓΟΡΙΑ ΤΙΜΗ

 Στείλτε μας E-MAIL στο: sales@dimoulas.com.gr με τα στοιχεία σας για την αποστολή της προσφοράς

 ΤΙΜΕΣ ΠΡΟΣΦΟΡΑΣ
 Η τιμή των 3-7 συσκ.
 ισχύει επίσης, αν 1
 συσκ. relay αγοράστεί
 με σύστημα plc

ARTICLE NUMBER		PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
KATHΓΟΡΙΑ	81,1	788 ΣΕΙΡΑ - 2U								
	788-304	20	BASE & RELAY 24VDC, AgNI 90/10, RED STATUS INDICATION, SPCO 1 (ON/ON), 16A	☐	☐	16	1	8,94	2,95	2,86
	788-312	20	BASE & RELAY 24VDC, AgNI 90/10, STATUS INDICATION, SPCO 2 (ON/ON), 2x8A	☐	☐	8	2	9,18	2,94	2,85
	788-354	20	BASE & RELAY (ALZ TYPE), 24VDC, STATUS INDICATION, SPCO 1 (ON/ON), 16A (FOR LAMPS)	☐	☐	16	1	14,17	3,68	3,54
	788-304/001-000	20	BASE & RELAY 24VDC, AgNI 90/10, GREEN STATUS INDICATION, SPCO 1 (ON/ON), 16A	☐	☐	16	1	8,94	4,02	3,93



Οι τιμές δεν περιλαμβάνουν φπα. και μεταφορικά

ΣΗΜΕΙΩΣΗ:

Σε περίπτωση οποιασδήποτε διαφοροποίησης των περιγραφών από αυτές του κατασκευαστή, υπερισχύουν πάντα οι περιγραφές του

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP . (A)	ΑΡ. ΕΠΑΦ .	PRICE ΚΑΤΑΛ	PRICE 1-2 Σ.	PRICE 3-7 Σ.
788-304/003-000	20	BASE & RELAY 24VDC, AgNI 90/10, RED STATUS INDICATION, SPCO 1 (ON/ON), 16A, DNV GL APPROVAL	☐	☐	16	1	10,68	4,81	4,70
788-312/003-000	20	** BASE & RELAY 24VDC, AgNI 90/10, STATUS INDICATION, SPCO 2 (ON/ON), 2x8A	☐	☐	8	2	10,91	4,91	4,80
788-324	15	RELAY SOCKET WITH RELAY DC 24 V, AgCdO, STATUS INDICATOR EACH 1 CHANGEOVER CONTACT (1U) 16A	☐	☐	16	1	11,96	5,38	5,26
788-341	15	RELAY SOCKET WITH RELAY DC 24 V AND STATUS INDICATOR, MANUAL OPERATION, 1 CHANGEOVER CONTACT (1U) 16A	☐	☐	16	1	14,86	5,94	5,80
788-346	15	RELAY SOCKET WITH RELAY DC 24 V AND STATUS INDICATOR, MANUAL OPERATION, 2 CHANGEOVER CONTACTS (2U) 2x8A (SINGLE SOCKET)	☐	☐	8	2	15,79	6,00	5,84
788-391	15	BASE & RELAY WITH RELAY, 24VDC, STATUS INDICATION, MANUAL OPERATION, SPCO 1 (ON/ON), 16A (RAILWAY APPLICATIONS)	☐	☐	16	1	14,86	6,69	6,54

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
788-355	15	Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 16 A; for lamp loads; Red status indicator; Module width: 15 mm: 2.50 mm²: grav	☐	☐	16	1	14,86	6,69	6,54
788-356	20	Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 16 A; for lamp loads; Red status indicator; Module width: 15 mm	☐	☐	16	1	15,55	7,00	6,84
788-390	15	Relay module; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; Path; Red status indicator; Module width: 15 mm	☐	☐	8	2	15,79	7,11	6,95
788-404	20	BASE & RELAY 24VDC, AgNI+Au, STATUS INDICATION, SPCO 1 (ON/ON), 16A (WITH GOLD CONTACTS MAX 50mA)	☐	☐		1	15,79	7,11	6,95
788-412	20	Relay module; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; with gold contacts; Red status indicator; Module width: 15 mm: 2.50 mm²: grav	☐	☐	8		16,94	7,62	7,45
788-357	20	Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 16 A; Red status indicator; Module width: 15 mm	☐	☐	16	1	17,18	7,73	7,56

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
	788-906	15	Relay module; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; Green status indicator; Module width: 15 mm	☐	☐	2	28,79	12,96	12,67
	788-384	15	Relay module with driven contacts; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 6 A; Red status indicator; Module width: 15	☐	☐	6	28,79	12,96	12,67
	788-700	20	RELAY SOCKET WITH SSR, CONTROL CIRCUIT: 18...30VDC, LOAD CIRCUIT: 0...24VDC, 3.5A, TURN-ON TIME 50 Ms, TURN OFF TIME 600 Ms	☐	☒	3,5	31,17	14,03	13,71
	788-720	20	Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 24 ... 240 VAC; Limiting continuous current: 1 A; 2-wire connection; zero-cross switching; Red status	☐	☒	1	32,85	14,78	14,45
	788-701	15	RELAY SOCKET WITH SSR, CONTROL CIRCUIT: 15...30VDC, LOAD CIRCUIT: 0...30VDC, 5A	☐	☒	5	38,23	17,20	16,82
ΚΑΤΗΓΟΡΙ 81,2 857 ΣΕΙΡΑ JUMPFLEX - 1U									
	857-304	25	JUMPFLEX RELAY TERMINAL BLOCK 20,4-28,8 VDC 10mA 1 CHANGEOVER CONTACT (1U) (ON/ON) 6A	☐	☐	1	15,73	4,09	3,93

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
857-354	25	JUMPFLEX RELAY TERMINAL BLOCK 20,4-28,8 VAC/DC 8.5mA, LED INDICATION, 1 CHANGEOVER CONTACT (1U) (ON/ON) 6A, EX	☐	☐		1	18,29	4,39	4,39
857-314	25	JUMPFLEX RELAY TERMINAL BLOCK 24 V DC 10mA, 1 CHANGEOVER (GOLD LAYER) CONTACT (1U) (ON/ON) 50mA (6A)	☐	☐		1	16,88	4,39	4,22
857-704	1	Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 0 ... 48 VDC; Limiting continuous current: 0.1 A; Yellow status indicator: Module width: 6 mm:	☐	☒	0,1		22,29	5,80	5,80
857-714	25	Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 24 ... 240 VAC; Limiting continuous current: 2 A; 2-wire connection; zero-cross switching: Yellow	☐	☒	1		31,46	8,49	8,18
857-724	25	JUMPFLEX RELAY SOCKET WITH SSR CONTROL CIRCUIT: 24VDC, LOAD CIRCUIT: 0...24VDC, 2A	☐	☒	2		31,58	9,79	9,47
857-624	1	JUMPFLEX MULTIFUNCTION TIME RELAY WITH SSR, (ON-DELAY, SINGLE-SHORT LEADING EDGE, BLINKING) CONTROL CIRCUIT: 24VDC, LOAD CIRCUIT: 0...24VDC. 2A. TURN ON TIME	☒	☐	2	1	63,63	28,63	28,00

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
	857-640	1	JUMPFLEX MULTIFUNCTION TIMING RELAY WITH 1 CHANGEOVER CONTACT (1U) (ON/ON) 6A, 8 TIME RANGES, 14 FUNCTIONS (FOR RAILWAY OPERATIONS)	☒	☐	1	107,80	48,51	47,43
	857-642	1	JUMPFLEX MULTIFUNCTION TIMING RELAY WITH 1 CHANGEOVER CONTACT (1U) (ON/ON) 6A, 8 TIME RANGES, 7 FUNCTIONS, 2 ADJUSTABLE TIME RANGES (FOR RAILWAY	☒	☐	1	118,60	53,37	52,18
KATHΓΟΡΙ 81,3 859 ΣΕΙΡΑ - 1U									
	859-304	10	RELAY TERMINAL BLOCK 20,4-26,4 VDC 10mA 1 CHANGEOVER CONTACT (1U) (ON/ON) 5A	☐	☐	5	15,73	3,15	3,15
KATHΓΟΡΙ 81,4 858 ΣΕΙΡΑ - INDUSTRIAL RELAYS									
	858-304	5	SOCKET WITH INDUSTRIAL RELAY, MANUAL OPERATION, LED INDICATION, COIL DC 24 V, 4 CHANGEOVER CONTACTS 5A	☐	☐	5	16,02	5,45	5,29
	858-314	5	SOCKET WITH INDUSTRIAL RELAY, MANUAL OPERATION, LED INDICATION, COIL DC 24 V, 4 CHANGEOVER (GOLD) CONTACTS 5A	☐	☐	5	18,91	8,51	8,32

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
858-324	5	SOCKET WITH INDUSTRIAL RELAY, MANUAL OPERATION, LED INDICATION, COIL DC 24 V, 2 CHANGE OVER CONTACTS 2x12A	☐	☐	12	2	19,30	8,69	8,49
 858-390	5	SOCKET WITH INDUSTRIAL RELAY, MANUAL OPERATION, LED INDICATION, COIL DC 24 V, 4 CHANGE OVER CONTACTS 6A, NO MARKABLE HOLDING BRACKET	☐	☐	6	4	25,30	11,39	11,13
ΚΑΤΗΓΟΡΙ 81,5		2042 ΣΕΙΡΑ - ΓΙΑ ΤΟΠΟΘΕΤΗΣΗ ΣΕ (ΕΙΔΙΚΕΣ) ΚΛΕΜΜΕΣ ΣΕΙΡΑΣ TOPJOB S							
 2042-3004	6	RELAY PLUG 24 VDC, LED INDICATION, 1 MAKE CONTACT (ON/OFF), 6A	☐	☐	6	1	24,91	11,21	10,96
 2042-3034	4	RELAY PLUG 24 VDC, LED INDICATION, 1 CHANGE OVER CONTACT (ON/ON), 10A	☐	☐	10	1	30,63	13,78	13,48
 2042-3044	4	RELAY PLUG 24 VDC, LED INDICATION, 2 CHANGE OVER CONTACT (ON/ON), 8A	☐	☐	8	2	41,09	18,49	18,08

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP . (A)	ΑΡ. ΕΠΑΦ .	PRICE ΚΑΤΑΛ	PRICE 1-2 Σ.	PRICE 3-7 Σ.
ΚΑΤΗΓΟΡΙΑ 81,6		789 ΣΕΙΡΑ - DIN / PANEL							
	789-304	10 RELAY MODULE 24VDC WITH 1 CHANGEOVER CONTACT (ON/ON) 12A	☐	☐	12	1	31,91	20,74	20,10
	789-323	10 RELAY MODULE 24VDC, 1 MAKE CONTACT 16A, MANUAL/OFF/AUTO SWITCH	☐	☐	16	1	35,63	23,16	22,09
	789-326	10 Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 12 A; for lamp loads; Manual/OFF/Auto switch; Red status indicator: Module width:	☐	☐		1	36,41	23,67	22,94
	789-312	10 RELAY MODULE 24VDC WITH 2 CHANGEOVER CONTACT (ON/ON) 8A	☐	☐	8	2	38,64	25,12	23,96
	789-325	10 RELAY MODULE 24VDC, WITH ISOLATED MONITORING CONTACT, 1 MAKE CONTACT 16A, MANUAL/OFF/AUTO SWITCH	☐	☐	16	1	41,45	26,94	25,70
	789-329	10 RELAY MODULE 24VDC, WITH SWITCH POSITION MONITORING CONTACT, 1 CHANGEOVER CONTACT 12A, MANUAL/OFF/AUTO SWITCH	☐	☐	12	1	42,30	27,50	26,23

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP (A)	ΑΡ. ΕΠΑΦ.	PRICE ΚΑΤΑΛ.	PRICE 1-2 Σ.	PRICE 3-7 Σ.
	789-324	10	Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 16 A; for lamp loads; Manual/OFF/Auto switch; Red status indicator: Module width:	☐	☐	1	45,62	29,65	28,74
	789-571	10	LATCHING RELAY MODULE 24VDC WITH 1 MAKE CONTACT (ON/OFF) 16A	☐	☐	16	48,98	31,84	30,37
ΚΑΤΗΓΟΡΙ 81,9 ΠΑΡΕΛΚΟΜΕΝΑ (788, 858, 859 κλπ)									
	788-154	20	PLUGGABLE MINIATURE SWITCHING RELAY, 24 VDC, 1 CHANGEOVER CONTACT (ON/ON), 16A	☐	☐	16	3,84	1,73	1,69
	788-156	20	Basic relay; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; Module width: 13 mm; Module height: 15 mm	☐	☐	8	3,84	1,73	1,69
	857-152	20	PLUGGABLE MINIATURE SWITCHING RELAY 24 VDC, 1 CHANGEOVER CONTACT (1 U)	☐	☐	6	5,57	2,51	2,45
	858-150	3	PLUGGABLE RELAY 24VDC 4 ON/ON, 5A	☐	☐	5	5,69	2,56	2,50

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP . (A)	ΑΡ. ΕΠΑΦ .	PRICE ΚΑΤΑΛ	PRICE 1-2 Σ.	PRICE 3-7 Σ.
857-153	20	Basic relay; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 6 A; with gold contacts; Module width: 5 mm; Module height: 15 mm	☐	☐		1	6,27	2,82	2,76
788-155	20	Basic relay; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 16 A; with gold contacts; Module width: 13 mm; Module height: 15 mm	☐	☐	16	1	6,38	2,87	2,81
788-157	20	Basic relay; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; with gold contacts; Module width: 13 mm; Module height: 15 mm	☐	☐	8	2	6,73	3,03	2,96
858-152	3	PLUGGABLE RELAY WITH GOLD CONTACTS 24VDC 4 ON/ON, 5A	☐	☐	5	4	7,77	3,50	3,42
857-164	20	Basic solid-state relay; Nominal input voltage: 24 VDC; Output voltage range: 0 ... 48 VDC	☐	☒	3		13,80	6,21	6,07
857-161	20	Basic solid-state relay; Nominal input voltage: 24 VDC; Output voltage range: 0 ... 24 VDC; Limiting continuous current: 3 A	☐	☒	3		23,11	10,40	10,17

ΤΙΜΕΣ ΠΡΟΣΦΟΡΑΣ
Η τιμή των 3-7 συσκ.
ισχύει επίσης, αν 1
συσκ. relay αγοράστεί
με σύστημα plc.

ARTICLE NUMBER	PACK UNIT	DESCRIPTION_ENG	TIMER REL.	SSR	OUTP . (A)	ΑΡ. ΕΠΑΦ .	PRICE ΚΑΤΑΛ	PRICE 1-2 Σ.	PRICE 3-7 Σ.
857-167	20	Basic solid-state relay; Nominal input voltage: 24 VDC; Output voltage range: 24 ... 240 VAC; Limiting continuous current: 2 A	☐	☒	2		23,11	10,40	10,17